




VISTA PROTOS³

STANDARD RANGE OF CAMERAS



VPC9032 camera door open

IDEAL FOR APPLICATIONS SUCH AS:

- Retail / Commercial Environments
- Prestigious new buildings
- Offices
- Bars and clubs



VPC9032 back

PROTOS³, THE COMPLETE CAMERA SOLUTION

The Vista Protos³ Standard Range of professional CCTV cameras consists of standard and high resolution, monochrome and colour cameras. This popular range of cameras offers 10 models, allowing the installer to choose the camera to meet the exact needs of the installations requirements.

Easy access to multiple function settings is gained via a drop down door located on the side of the camera. With quick connect facility for AI lens use, and wide ranging power supply for low and high voltage variants, the Vista Protos³ Standard range of cameras provide high quality images and functionality to suit any requirement.

THE UK'S PREMIER CCTV BRAND



TECHNICAL SPECIFICATIONS

	VPM8030	VPM8130	VPM8120	VPC9030	VPC9130
	VPM8032	VPM8132	VPM8122	VPC9032	VPC9132
GENERAL:					
SENSOR	1/3" Super HAD		1/2" Super HAD	1/3" Super HAD	
TYPE	Monochrome			Colour	
EFFECTIVE PIXELS (H X V)	500 x 582	752 x 582		500 x 582	752 x 582
SENSITIVITY	0.06 Lux	0.07 Lux	0.06 Lux	0.6 Lux	0.7 Lux
RESOLUTION	380 TV Lines	580 TV Lines		330 TV Lines	480 TV lines
VIDEO OUTPUT	1V pk-pk composite video via 75 Ω BNC connector on rear of camera				
CCIR	625 lines of 50 fields per second, 2:1 interlace				
SIGNAL TO NOISE RATIO	Better than 50dB			Better than 48dB	
WHITE BALANCE	N/A			Auto tracing	
AGC	Built-in 28dB				
BLC	Selectable on / off. Weighted to centre third of screen				
GAMMA	Selectable gamma of 0.45 normal or 1.0 linear via dip switch				
SYNC. SYSTEM	Line lock. Option to switch to internal is provided via dip switch				
ADJUSTABLE V PHASE	$\pm 120^\circ$				
LENS OPTIONS	C/CS mount				
AUTO IRIS (VID. DRIVE)	Via 3 way. two part terminal block at rear of camera				
AUTO IRIS (DC DRIVE)	4 pin square (Chausemen) plug				
POWER:					
MAINS VERSION VOLTAGE	98~260V AC				
LOW VOLTAGE VERSION	11~40V DC, or 14~30V AC				
MAINS CONSUMPTION	<7W				
LOW VOLTAGE CONSUMPTION	<4W				
PHYSICAL:					
MATERIAL	Die-cast zinc lens mount, extruded aluminium body, flame retardant ABS plastic front trim, rear bezel and door				
LENS MOUNT	C/CS via tracking focus mechanism with two adjustment points (top & sides)				
CAMERA MOUNT	1/4" - 20 UNC or 1/4" BSW (top or bottom)				
OPERATING TEMP.	-10 $^\circ$ ~ +50 $^\circ$ C (14 ~ 122 $^\circ$ F)				
CAMERA DIMS. (LXWXH)	130 x 67 x 60mm				
GROSS WEIGHT	0.5Kg				

ORDERING INFORMATION

VPM8030	1/3' MEDIUM RESOLUTION MONOCHROME CAMERA, 0.06 LUX, 380 TVL, 98~260V AC
VPM8032	1/3' MEDIUM RESOLUTION MONOCHROME CAMERA, 0.06 LUX, 380 TVL, 11~40VDC OR 13~30V AC
VPM8130	1/3' HIGH RESOLUTION MONOCHROME CAMERA, 0.07 LUX, 580 TVL, 98~260V AC
VPM8132	1/3' HIGH RESOLUTION MONOCHROME CAMERA, 0.07 LUX, 580 TVL, 11~40V DC OR 13~30V AC
VPM8120	1/2' HIGH RESOLUTION MONOCHROME CAMERA, 0.06 LUX, 580 TVL, 98~260V AC
VPM8122	1/2' HIGH RESOLUTION MONOCHROME CAMERA, 0.06 LUX, 580 TVL, 11~40V DC OR 13~30V AC
VPC9030	1/3' MEDIUM RESOLUTION COLOUR CAMERA, 0.6 LUX, 330 TVL, 98~260V AC
VPC9032	1/3' MEDIUM RESOLUTION COLOUR CAMERA, 0.6 LUX, 330 TVL, 11~40V DC OR 13~30V AC
VPC9130	1/3' HIGH RESOLUTION COLOUR CAMERA, 1 LUX, 480 TVL, 98~260V AC
VPC9132	1/3' HIGH RESOLUTION COLOUR CAMERA, 0.7 LUX, 480 TVL, 11~40V DC OR 13~30V AC

DISTRIBUTED BY:

ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE



VISTA NORBAIN HOUSE, ESKDALE ROAD, WINNERSH TRIANGLE, WOKINGHAM, BERKSHIRE. RG41 5TS
 TELEPHONE: +44 (0) 118 944 0123 FAX: +44 (0) 118 944 0999
 WEBSITE: WWW.VISTA-CCTV.COM

DATASHEET VERSION: MARCH 2003