

P-19



▶ FEATURES

- NeoV Optical Glass™
- Swift 4ms response time
- Crisp 700 contrast ratio
- High 300 brightness
- DVI ready for high quality signal
- S-Video and CVBS video inputs
- 4 USB ports for easy connection
- Built-in 3D stereo speakers and subwoofer
- Intuitive NeoMatch™ OSD design
- Headphone jack and microphone jack
- Supports sRGB mode
- Auto-adjustment for optimal setting
- Kensington® security slot
- VESA standard wall mount

▶ SPECIFICATION

Panel	Panel Type	TFT LCD
	Panel Size	19.0" (483mm)
	Max. Resolution	SXGA 1280 x 1024
	Pixel Pitch	0.294mm
	Brightness	300cd/m ² (Typical)
	Contrast Ratio	700:1 (Typical)
	Surface Treatments	Hard Coating (3H), Anti-glare Treatment
	Viewing Angle (H/V)	160°/155° (Typical)
	Display Color	16.7M
	Response Time	3ms (GTG)
	Frequency (H/V)	H: 31.5kHz - 80kHz V: 50Hz - 75Hz
	Max. Pixel Clock	140MHz
	Life Time	50,000hrs (Minimum)
Input	Analog	15-Pin D-Sub
	Digital	29-Pin DVI-D
	S-Video*	4-Pin Mini Din S-Video
	CVBS*	CVBS Jack
USB Port	Upstream	1 (USB 2.0)
	Downstream	4 (USB 2.0)
Audio	Speaker	2W x 2
	Subwoofer	4W x 1
	Audio In	3.5mm Audio Line-in
	Audio Out	3.5mm Headphone Jack
	Microphone In	3.5mm Audio Line-in
	Microphone Out	3.5mm Headphone Jack
Connector	Power	3-Pin AC Plug
NeoV Optical Glass	Thickness	3.0mm (0.18")
	Reflection Rate	<1%
	Transmission Rate	>96%
	Hardness	>6H (MOH's Rating)
Tilt	Tilt	+10° ~ +30°
Mounting	VESA FPMPI	Yes (100mm)
Regulation Approval	Safety & EMI	UL/CUL, TUV/GS, CCC, TCO 99, GOST, FCC, CE, BSMI, EPA, CSA, ISO 13406-2
	VESA	DDC/CI, DDC/2B, DPMS
Power	Power AC	100 - 240V, 50 - 60Hz
	Consumption	<70W (On) <2W (Stand-by) <1W (Off)
	Net (W x H x D)	439 x 421 x 188mm (17.3" x 16.6" x 7.4")
Dimensions	Packing (W x H x D)	TBA TBA
	Net Weight	7.7Kg (17.0lbs)
Weight	Gross Weight	TBA
	1 Pallet	TBA
Packing	20' Container	TBA
	40' Container	TBA

*Video inputs are optional functions

All specifications are subject to change without prior notice